


Adelaide Black GRANITE

TECHNICAL SPECIFICATIONS



Flamed finish

ADELAIDE BLACK GRANITE



Flamed

ADELAIDE BLACK is one of Australia's premier granites. It has been used extensively across a numerous amount of large commercial projects.

Dimension stone is a product of nature and is subject to variation in colour and texture.

Images are a guide only, we recommend ordering a sample or generally full size slabs are available to view on request.



TECHNICAL SPECIFICATIONS

DETAILS

Name:	Adelaide Black
Substitute Names:	
Colour & veining:	Gabbro
Quarry Location:	Black Hill, South Australia
Availability:	Excellent

TYPICAL PHYSICAL PROPERTIES

Bulk Density :	2.97 tonnes/m ³
Compressive Strength (dry/wet):	217/193 MPa
Flexural Strength (dry/wet):	17.7/15.5MPa
Water Absorption by weight:	0.03%
Abrasion Resistance:	Taber index 26
Slip resistance:	Flamed & Blasted; Class V - Very low risk of slipping Honed: Class X - Moderate risk of slipping

PHYSICAL CHARACTERISTICS

Texture:	Fine grained black
Inclusions:	None
Degree of polish:	High
Variation of Tonality:	Consistent background with occasional whitish flairs
Characteristics:	Fine grained
Finishes available:	Polished, Honed, Flamed, Blasted and Satin
Forms Available:	Blocks, Slabs, Pavers, Cobbles and cut to size panels

PETROGRAPHIC ANALYSIS

Plagioclase:	67%
Clinopyroxene (Augite)	15%
Orthopyroxene:	10%
K Feldspar:	5%
Biotite:	1%
Ilmenite	1%
Other minerals:	1%

Head Office - Wingfield 122 South Terrace, Wingfield, SA 5013 T: +61 8 8345 1842

Mile End Showroom 333 South Road, Mile End, SA 5031 T: +61 8 8352 1265

City Store - Architectural Showroom 100a Flinders Street, Adelaide SA 5000
T: +61 8 8232 7633 (By appointment only)

AMS Surfaces Showroom 72 Mortlock Tce, Port Lincoln, SA 5607 T: +61 8 8682 0000

enquiries@adelaidemarble.com.au | amssurfaces.com.au